

# PFINDER 895 REMOVER



Version 11 | 15.07.2022 | Page 1/1

## DESCRIPTION

PFINDER 895 is a special cleaner based on isopropanol for penetrant and magnetic particle testing. PFINDER 895 is used as precleaner for removal of oils and greases from the surface to be tested or as approved remover of PFINDER penetrants.

PFINDER 895 is particularly suitable for general cleaning and removal of oils and greases. Material compatibility (e.g. for plastics) has to be checked beforehand.

Remover method C according EN ISO 3452-1.

## APPLICATION

For precleaning or as all-purpose cleaner: Apply PFINDER 895 to the surface to be cleaned, if necessary allow time to react and if required wipe off with a cloth.

For excess penetrant removal: Spray PFINDER 895 on a cloth and clean surface to be tested. Do not spray directly on the surface!

The capability of the penetrant system should be checked regularly by means of own reference pieces or e.g. reference test block 2 according EN ISO 3452-3.



## YOUR GREEN NDT BENEFITS

- | Mild odour
- | Aerosol spray can with minimized carbon footprint



## YOUR HANDLING + COST SAVING BENEFITS

- | Powerful cleaner
- | All-purpose use

## APPROVALS & CONFORMITIES

The product conforms to these specifications / is suitable for the use according to:

EN ISO 3452-2 | ASTM E165 |  
ASME V Art.6 | PMUC | ASTM E1417

Low content of sulfur and halogens  
according to EN ISO 3452-2.

## PACKAGING

500-ml-spray can (for 360° application)

These packages are on stock and instantly available. Other packages on demand.

## SHELF-LIFE & STORAGE

3 years

Storage between +5°C and +45°C.

CHARACTERISTIC DATA	Specification	Unit	Value
Density/20°C*	DIN 51 757	kg/m <sup>3</sup>	approx. 785 ± 15
Flash Point*	EN ISO 2719	°C	< 15

\* Data of products packaged in aerosol spray cans might differ.